

EOLE 2



Expression. **Emotion.** Experience.

With a new design for improved esthetical and acoustical integration, the EOLE 2 system features all the acoustical qualities of any Cabasse system: efficiency, power handling, transparency and stability of the sound stage.


Consisting in 5 new spherical satellites only 13 cm in diameter that swivel in every direction thanks to a magnetic base and a very compact subwoofer, EOLE 2 took advantage in many respects of the research investments made in developing La Sphère, the Cabasse 4-way coaxial reference speaker.

Opera, jazz festival, rock concert, movies, be blown away by EOLE 2.

Cabasse
www.cabasse.com

EOLE 2

YOUR CABASSE DEALER



IN CEILING VERSION



ON WALL



ON BASE



EOLE 2 FLOORSTANDING



SANTORIN 21 SUBWOOFER

EOLE 2

	EOLE 2 Satellite	SANTORIN 21 Subwoofer	EOLE 2 in ceiling
Use	on wall / on base	floor standing	in ceiling / in wall
Ways	2	1	2
Drivers	2-way coaxial driver : 1 x DOM18: 29 mm (1.1") soft dome tweeter 1 x 10T15: 10 cm (4") P2C midrange-woofer	1 x 21MT3 : 21cm (8") ICF woofer	2-way coaxial driver : DOM18: 29 mm (1.1") soft dome tweeter 10T15: 10 cm (4") P2C midrange-woofer
Efficiency 1 W/1 m	91 dB	active	91 dB
Cross-over points	4,000 Hz	adjustable 20 - 200 Hz	4,000 Hz
Phase	-	adjustable 0° - 180°	-
Frequency bandwidth	170 - 22,000 Hz	35 - 200 Hz	170 - 22,000 Hz
Nominal impedance	8 ohms	active	8 ohms
Minimal impedance	4,3 ohms	active	4,3 ohms
Power handling / Peak power	70 / 490 W	250 / 750 W	70 / 490 W
Magnetic shielding	yes	no	yes
Dimensions (H x B x T)	Ø 13 Ø 6.5"	33 x 33 x 36 13" x 13" x 14.2"	Ø 20 7.87"
Weight	1.3 kg / 2,9 lbs	11.5 kg / 25 lbs	-
Finish	Glossy black, glossy white	Glossy black, white	White

Cabasse
www.cabasse.com